

# ETC Unison Echo Dual Tech Occupancy and Vacancy Sensors

## Echo Responsive Control Series



### GENERAL INFORMATION

Buildings waste electricity as a result of lights being left on in an unoccupied room. Occupancy and Vacancy Sensors are a convenient and simple solution for any facility to eliminate wasted energy by automatically turning off lighting loads when a room is empty. The low-profile, sleek sensors can be installed anywhere to provide uninterrupted, 24/7/365 operation, without affecting the look and beauty of their surroundings.

#### APPLICATIONS

- Houses of worship
- Education
- Hospitality
- Healthcare facilities
- Office buildings
- Conference rooms
- Meeting rooms
- Retail

#### FEATURES

- Manual-on/auto-off (Vacancy Sensor) and auto-on/off (Occupancy Sensor) versions
- Multi Space Preset functionality
- Passive infrared (PIR) and Acoustic sensing technology
- Two mounting options available:
  - Ceiling-Mount
  - Wall-Mount
- Multiple Lensing options available
- Walk-thru mode for coverage verification
- Field-installed coverage masks (Ceiling only)
- EchoConnect: two-wire, topology-free bus for power and communication
- Ceiling Sensor available in black and white
- Wall Sensor version available in cream, black and white

#### REGULATORY AND COMPLIANCE

- cULus Listed
- CE Certified

### ORDERING INFORMATION

#### Ceiling Mount Occupancy and Vacancy Sensors

MODEL	DESCRIPTION
E-DOC-C-SR-__	Dual Tech Occupancy Sensor - Small Room
E-DOC-C-LR-__	Dual Tech Occupancy Sensor - Large Room
E-DOC-C-HC-__	Dual Tech Occupancy Sensor - High Ceiling
E-DVAC-C-SR-__	Dual Tech Vacancy Sensor - Small Room
E-DVAC-C-LR-__	Dual Tech Vacancy Sensor - Large Room

Enter sensor color code in \_\_ space provided:

4 = Black (RAL 9004), 5 = Pure White (RAL 9010)

#### Wall Mount Occupancy and Vacancy Sensors

MODEL	DESCRIPTION
E-DOC-W-NR-__	Dual Tech Occupancy Sensor - Narrow Wall
E-DOC-W-WD-__	Dual Tech Occupancy Sensor - Wide Wall
E-DVAC-W-NR-__	Dual Tech Vacancy Sensor - Narrow Wall
E-DVAC-W-WD-__	Dual Tech Vacancy Sensor - Wide Wall

Enter sensor color code in \_\_ space provided:

1 = Cream (RAL 9001), 4 = Black (RAL 9004), 5 = Signal White (RAL 9003)

#### Echo Power Requirements

EchoConnect:	1 Unit of Control Power
Auxiliary Power:	Not Required



# ETC Unison Echo® Dual Tech Occupancy and Vacancy Sensors

## Echo Responsive Control Series

### SPECIFICATIONS

#### FUNCTIONAL

- Occupancy sensors support configurable auto-on/auto-off functionality (occupancy sensing) functions
- Vacancy sensors support configurable manual-on/auto-off (vacancy sensing) functions
- Ceiling Sensor:
  - 360-degree coverage pattern
  - Includes configurable coverage masks
  - Small room: 450 sq. ft. at 8' ceiling, 800 sq. ft. at 12' ceiling
  - Large room: 1800 sq. ft. at 8' ceiling, 3000 sq. ft. at 12' ceiling
  - High ceiling: 300 sq. ft. at 10' ceiling, 7000 sq. ft. at 40' ceiling
- Wall Sensors
  - Wide: 60' coverage at 7-10' mounting height. 140 degree field of detection
  - Narrow: 16' by 75' coverage pattern at mounting height of 7-10'. 40 degree field of detection
- Supports walk-thru mode for verifying coverage area
  - Sensor lens illuminates for walk-thru and test mode
  - Red illumination for PIR detection
  - Green illumination for Acoustic detection
- Sensor coverage tested to NEMA WD 7-2000

#### MECHANICAL

- Constructed of injection-molded, ABS plastic in Pure White (RAL9010) or Black (RAL 9004) or Cream (RAL 9003 - Wall only)
- Electronics assembly and mounting accessories included
- Accessible configuration buttons
- No visible means of attachment
- Ceiling Mount:
  - Surface- or box-mountable
  - Supports drywall, plaster, wood and concrete mounting
  - Mounts to standard electrical box (supplied by others)
  - Mounts to compressed fiber ceilings with included wire mounting option
- Wall Mount:
  - Flush-mount to industry standard backbox, RACO 690 or equivalent

#### ELECTRICAL

- Connect via EchoConnect two-wire control network utilizing low-voltage Class 2 wiring
  - Topology-free and polarity-independent wiring over Belden 8471 or equivalent and one #14 ESD drain wire
  - Wiring may be bus, loop, home run or any combination of these
- Up to 500 meters (1,640 feet) of control wiring per system
- Supports optional Cat5/5e wiring using Belden 1583A or equivalent
  - Requires optional Cat5 termination accessories

#### ENVIRONMENTAL

- Ambient room temperature: 0–40° C / 32–104° F
- Ambient humidity: Maximum 90% non-condensing

### FUNCTIONALITY

#### BASIC MODE FUNCTIONALITY

- Occupancy Sensors
  - Occupancy Event: Play selected default preset
  - Vacancy Event: Space off
- Vacancy Sensor:
  - Occupancy Event: N/A
  - Vacancy Event: Space off

#### CUSTOM MODE FUNCTIONALITY

(Requires Programming With EchoAccess® Mobile App and additional connection hardware)

- Occupancy Events Supported
  - Preset Activate\*
  - Zone Set to Level
  - Space Set to Level
- Vacancy Events Supported
  - Preset Activate\*
  - Zone Set to Level
  - Space Set to Level
  - Space Off\*

\*Multi Space capable - allowing for presets to be recalled in multiple spaces from a single control

# ETC Unison Echo Dual Tech Occupancy and Vacancy Sensors

## Echo Responsive Control Series

### ECHO FAMILY OF PRODUCTS

#### EchoConnect Power Supplies

MODEL	DESCRIPTION
E-SPS	6U Room Station Power Supply, Knockout Mount
E-SPS-DIN	16U DIN rail Station Power Supply with 24V Aux
E-SPM	16U DRd Station Power Module
E-SPM-A	16U DRd Station Power Module with 24V Aux
E-SPM-RM	16U Rack-Mount Station Power Module Aux
E-SPM-RM-A	16U Rack-Mount Station Power Module 24V Aux
E-SPM-WM	16U Wall-Mount Station Power Module
E-SPM-WM-A	16U Wall-Mount Station Power Module 24V Aux
E-APS	24V Aux Power Supply, Knockout Mount

#### EchoTouch

MODEL	DESCRIPTION
ETS	EchoTouch Controller

#### Echo Stations

MODEL	DESCRIPTION
E1001	Inspire One Button Station
E1002	Inspire Two Button Station
E1004	Inspire Four Button Station
E1006	Inspire Six Button Station
E1008	Inspire Eight Button Station
E1104	Inspire Four Button with Fader Station
EPS05	Echo Preset Station - 5 Button
EPS10	Echo Preset Station - 10 Button
EPSKS	Echo Keyswitch Station
E-ATC	Echo TimeClock

#### Echo Responsive Controls

MODEL	DESCRIPTION
ELS	Light Sensor
EOCC	Ceiling-Mount PIR Occupancy Sensor
EVAC	Ceiling-Mount PIR Vacancy Sensor
E-DOC-C	Ceiling-Mount Dual Tech Occupancy Sensor
E-DVAC-C	Ceiling-Mount Dual Tech Vacancy Sensor
E-DOC-W	Wall-Mount Dual Tech Occupancy Sensor
E-DVAC-W	Wall-Mount Dual Tech Vacancy Sensor
E-DOC-SM1	Switch-Mount Dual Tech Sensor - One Button
E-DOC-SM2	Switch-Mount Dual Tech Sensor - Two Button

#### Echo Interfaces

MODEL	DESCRIPTION
EACC	EchoAccess Interface
EEB	Echo Expansion Bridge
EDMXC	Echo DMX Scene Controller
EEl	Echo-Echoflex Interface
ECII	Echo Contact Input Interface
ECOI	Echo Contact Output Interface
EDRI	Echo Demand Response Interface
EBI	Echo BACnet Interface

#### Zone Controllers

MODEL	DESCRIPTION
ERC-G2	One Zone Relay Controller
EDRC-G2	Two Zone Relay Controller
ELD-G2	One Zone 0-10V Controller
EDLD-G2	Two Zone 0-10V Controller
ESSC-G2	One Zone SmartSpace Controller
EDSSC-G2	Two Zone SmartSpace Controller
ELVD-G2	600-Watt Phase Adaptive Dimmer
ELVD-277-G2	600-Watt Phase Adaptive Dimmer- 277V

#### Room Controllers

MODEL	DESCRIPTION
ERMC4-G2	Four Zone Room Controller
ERMCT4-G2	Four Zone Room Controller with TimeClock
ERMC8-G2	Eight Zone Room Controller
ERMCT8-G2	Eight Zone Room Controller with TimeClock

#### Panel Products

MODEL	DESCRIPTION
ERP	Echo Relay Panel Mains Feed
ERP-FT	Echo Relay Panel Feed Through
SensorIQ	Sensor IQ Intelligent Breaker System
SR3	Sensor3 Power Control System
DRd	Unison DRd with Echo Control


ETC

Unison Echo Dual Tech Occupancy and Vacancy Sensors


Echo Responsive Control Series

SAMPLE ECHO SYSTEMS

SAMPLE SENSOR RISER



SAMPLE PANEL BASED SYSTEM RISER






ETC

Unison Echo Dual Tech Occupancy and Vacancy Sensors

Echo Responsive Control Series


CEILING MOUNT COVERAGE PATTERNS




Echo Responsive Control Series

FLOOR COVERAGE PATTERNS


Small Room Floor Coverage  
For mounting height of 8 feet (2.4m)



Large Room Floor Coverage  
For mounting height of 8 feet (2.4m)



High Ceiling Floor Coverage  
For mounting height of 30 feet (12.2m)




ETC

Unison Echo Dual Tech Occupancy and Vacancy Sensors


Echo Responsive Control Series

WALL MOUNT COVERAGE PATTERNS

WALL MOUNT NARROW LENS



WALL MOUNT WIDE LENS



# ETC Unison Echo Dual Tech Occupancy and Vacancy Sensors

## Echo Responsive Control Series

### PHYSICAL


#### Sensor Dimensions\*

MODEL	HEIGHT		WIDTH		DEPTH	
	in	mm	in	mm	in	mm
E-DOC-C / E-DVAC-C	4.29	109	4.29	109	1.14	29
E-DOC-W / E-DVAC-C	3.32	84	2.76	70	3.34	85

#### Sensor Weights\*

MODEL	WEIGHT		SHIPPING WEIGHT	
	oz	g	oz	g
E-DOC-C / E-DVAC-C	3.84	109	6.24	177
E-DOC-W / E-DVAC-C	4.40	125	6.64	188

\*Weights and dimensions typical



Corporate Headquarters • Middleton, WI USA

Global Offices • London, UK • Rome, IT • Holzkirchen, DE • Paris, FR • Hong Kong • Singapore • New York, NY • Orlando, FL • Burbank, CA

Copyright©2019 ETC. All Rights Reserved. All product information and specifications subject to change. Rev C 08/19

Trademark and patent info: etconnect.com/IP

[etconnect.com](http://etconnect.com)